

Ultrafix CA SERIES

APPLICATIONS

Frame adhesive

GENERAL CHARACTERISTICS

- Spray-activated cyanoacrylate adhesives
- Mounts screen mesh onto aluminum, steel, iron, plastic-coated, and wood frames.
- Cure instantly
- Highly resistant to water and solvents
- Standard cyanoacrylate available in three viscosities — Ultrafix CA50, CA100, and CA150
- Ultrafix C-Flex is a toughened, more flexible version

DIRECTIONS FOR USE

To obtain optimal adhesion, degrease the frame. Stretch the fabric over the frame providing good contact between the two. Squeeze a thin bead of adhesive onto fabric around the frame perimeter and spread evenly. Lightly spray the applied adhesive with Ultrafix CA Activator A (aerosol) or Ultrafix CA Activator P (pump style), which sets in less than 30 seconds. Release tension and remove the screen from the stretching system.

Health & Safety

Before using, refer to appropriate material safety data sheets.

STORAGE

When sealed in the original container and stored in cool conditions, SaatiChem products will maintain their original properties for one year from the date of production.

PACKAGING

Ultrafix CA50, CA100, CA150, and C-Flex adhesives are available in 16 oz. containers.

Ultrafix CA Activator A is available in 10 oz. containers.

Ultrafix CA Activator P is available in 8 oz. and 1 gallon containers.

Product	For Use On Mesh Counts (threads/in)
Ultrafix CA50	330 – 508
Ultrafix CA100	196 – 380
Ultrafix CA150	17 – 196
Ultrafix C-Flex	305 – 460

WARRANTY & LIMITED REMEDY

The directions, recommendations, and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose:

All SaatiChem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in SaatiChem's applicable Product Bulletin. SaatiChem will replace or refund the price of any SaatiChem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall SaatiChem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special, or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.

To receive the Material Safety Data Sheet (MSDS), send an e-mail to: MSDS@saatichem.com

USA 1.877.296.7697 [Toll-free US & Canada] or 1.847.296.7697 e-mail: info.US@saatichem.com	Italy +39.031.9711 e-mail: info.IT@saatichem.com	China +86.21.58999113 or +86.21.58349020 e-mail: info.CN@saatichem.com	For More Information about SaatiChem visit our website: www.saatiamericas.com
---	--	---	--