

Ultrafix REMOVER

APPLICATIONS

Removes frame adhesives

GENERAL CHARACTERISTICS

- Remove Ultrafix adhesive residue from screen printing frames and other hard surfaces
- Available in liquid and convenient gel form

DIRECTIONS FOR USE

Stir Ultrafix Remover before use. Using a paintbrush, generously apply Ultrafix Remover Gel to the glue-covered surface or soak glue-covered surface in Ultrafix Remover Liquid. Allow it to stand for a minimum of one hour and longer for thicker coats of glue. Using a scraper, such as a paint scraper, remove Ultrafix Remover along with the loosened glue. Carefully rinse off excess before using a pressure washer to remove any remaining gel and loosened glue. Repeat if necessary.

Health & Safety

Before using, refer to appropriate material safety data sheets.

STORAGE

When sealed in the original container and stored in cool conditions, Saatichem products will maintain their original properties for one year from the date of production.

PACKAGING

Ultrafix Remover Gel is available in quart containers. *Ultrafix Remover Liquid* is available in quart, gallon, 5-gallon, and 50-gallon containers.

WARRANTY & LIMITED REMEDY

The directions, recommendations, and specifications contained in this Technical Data Sheet are meant as a guide to the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other expressed or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose:

All SaatiChem manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications stated in SaatiChem's applicable Product Bulletin. SaatiChem will replace or refund the price of any SaatiChem manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall SaatiChem be liable for any other direct or indirect damage or loss, including without limitation any incidental, special, or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or any other item.

To receive the Material Safety Data Sheet (MSDS), send an e-mail to: MSDS@saatichem.com

USA

1.877.296.7697 [Toll-free US & Canada]
or 1.847.296.7697
e-mail: info.US@saatichem.com

Italy

+39.031.9711
e-mail: info.IT@saatichem.com

China

+86.21.58999113
or +86.21.58349020
e-mail: info.CN@saatichem.com

For More Information

about SaatiChem
visit our website:
www.saatiamericas.com