



Becker™ Rigid

Custom-made to your exact requirements, these quality welded metal frames are much stronger than inferior wood frames, yet are conveniently lightweight and are more corrosion resistant. They are constructed with a surface ground or sandblast finish for excellent adhesion.

Choose from a wide variety of profiles as well as wall thicknesses to meet strength requirements.

FRAMES FOR STANDARD APPLICATIONS

MODEL	PROFILE THICKNESS	WALL THICKNESS	RECO MAX OD LENGTH
1	½" X 1"	0.125"	18"
2	¾" X ¾"	0.125"	18"-24"
3	¾" X 1½"	0.125"	31"-36"
4	1" X 1"	0.070"	18"-24"
5	1" X 1"	0.125"	24"-30"
6	1" X 1½"	0.125"	30"-36"
7	1" X 2"	0.125"	40"-45"
8	1¼" X 1¼"	0.095"	26"-30"
9	1¼" X 1¼"	0.125"	30"-35"
10	1½" X 1½"	0.070"	31"-36"
11	1½" X 1½"	0.095"	36"-40"
12	1½" X 1½"	0.125"	40"-50"
13	1½" X 2"	0.125"	50"-55"
14	1½" X 2½"	0.125"	55"-75"
15	1½" X 3"	0.125"	90"-105"
16	1½" X 4"	0.125"	120"-140"
17	1¾" X 5"	0.125"	200" & up
18	2" X 2"	0.125"	60"-70"
19	2" X 3"	0.125"	70"-80"
20	2" X 4"	0.125"	140"-160"
21	2" X 6"	0.125"	240" & up



247 Route 100
Somers, NY 10589

Phone: 800 / 431-2200
or 914 / 232-7781

Fax: 800/829-9939
or 914 / 232-4004

Info.US@saatiprint.com
www.saatiamericas.com